

## Fin2000 Slats

**Patented**

When you need extra privacy for commercial or industrial applications, our Fin2000 is the answer. This uniquely styled, patented slat can be purchased by the bag or pre-inserted into the chain link wire during the weaving process.

**Design** – Flat tubular plastic with fins for added privacy.

**Durability** – The Fin2000 is resistant to severe weather conditions, salt, water, sand, road dirt, most acids, alcohol, alkaline, ammonia, petroleum distillates, and common environmental pollutants.

**Installation** – Insert the slats vertically into the fence from top to bottom. No tools are necessary. The wings grip the knuckles of the wire mesh securing the slat in place.

**Standard Heights** – 4 ft., 5 ft., 6 ft., 7 ft., 8 ft., 10 ft. and 12 ft.  
*Special heights available upon request*

**Upon Special Request** – Available in bags that cover 25 linear feet for hand installation jobs.

**Wind Load and Privacy Factor** – Approximately 98% (Based on wire/mesh used-stretch tension)

**Colors** – Beige, Redwood, Black, White, Royal Blue, Forest Green, Gray, Dark Brown, Sky Blue

### Features and Benefits

**Materials** – slats are extruded from High Density Polyethylene (HDPE), color pigments and ultra violet (UV) inhibitors specifically formulated to retard the harmful effects of the sun and lengthen the life of the slat.

**Durability** – Our slats are also resistant to severe weather conditions, salt water, sand, road dirt, most acids, alcohol, alkaline, ammonia, petroleum distillates, and common environmental pollutants.

**Maintenance** – Our slats are nearly maintenance free. They may be pressure cleaned of surface contaminants with plain water.

**Wind Load Disclaimer** – We will not be held responsible for fence damage resulting from wind load conditions due to insufficient structural support.

**Designations** – Meets ASTM Designation: F3000/F3000M (except HedgeLink and Aluminum Slat)

### HDPE Technical Properties

Property	Values
Melt Index	(.6) A low melt index indicates improved stress and crack resistance.
Density	(.957) Polyethylene ranges anywhere from .914 to .960 in density. A higher density yields maximum stiffness without becoming overly brittle.
Minimum Temp.	(-76° F) Polyethylene stays flexible even at this temperature extreme.
Maximum Temp.	(250° F) Polyethylene does not distort until reaching this temperature.
Tensile Strength	(3,700 psi) Material will not suffer distortion at lesser loads or impacts.



Slat Name	Slat Width	Mesh Size	Wire Gauge	Coverage Area
Fin2000	2 13/16"	3 1/2 x 5" only	9 or 10 gauge only	25 Linear feet

### Available Colors

(colors are approximations)



Exact representation of colors in printing is difficult. Please refer to actual color samples for accurate matching. **Samples available upon request.**