



Ultimate Slat™ Patented

Ultimate Slat™ provides more privacy than any other double-wall slat. This top-locking slat combines the proven quality and durability of our standard slats with four unique “wings” for extra screening and security.

Design – Includes a rigid, flat tubular body with inside legs for extra support. These flexible and resilient four wing portions are positioned two on each side of the slat body. There are no serrations thereby giving a more beautiful, esthetic look.

Standard Heights – 4 ft., 5 ft., 6 ft., 7 ft., and 8 ft.
Special heights available upon request

Slat Length – 2” shorter than the overall height of the fence

Wind Load and Privacy Factor – Approximately 98% on 2” mesh and approximately 90% on 2 1/4” mesh (Based on wire/mesh used-stretch tension)

Colors – Beige, Redwood, Black, White, Royal Blue, Forest Green, Gray, Dark Brown, Sky Blue

Features and Benefits

Materials – slats are extruded from High Density Polyethylene (HDPE), color pigments and ultra violet (UV) inhibitors specifically formulated to retard the harmful effects of the sun and lengthen the life of the slat.

Durability – Our slats are also resistant to severe weather conditions, salt water, sand, road dirt, most acids, alcohol, alkaline, ammonia, petroleum distillates, and common environmental pollutants.

Maintenance – Our slats are nearly maintenance free. They may be pressure cleaned of surface contaminants with plain water.

Wind Load Disclaimer – We will not be held responsible for fence damage resulting from wind load conditions due to insufficient structural support.

Designations – Meets ASTM Designation: F3000/F3000M (except HedgeLink and Aluminum Slat)

HDPE Technical Properties

Property	Values
Melt Index	(.6) A low melt index indicates improved stress and crack resistance.
Density	(.957) Polyethylene ranges anywhere from .914 to .960 in density. A higher density yields maximum stiffness without becoming overly brittle.
Minimum Temp.	(-76° F) Polyethylene stays flexible even at this temperature extreme.
Maximum Temp.	(250° F) Polyethylene does not distort until reaching this temperature.
Tensile Strength	(3,700 psi) Material will not suffer distortion at lesser loads or impacts.

Slat Name	Slat Width	Mesh Size	Wire Gauge	Coverage Area
Ultimate Slat 2”	1 7/16”	2”	9	10 linear feet
Ultimate Slat 2 1/4”	1 7/16”	2 1/4”	11	10 linear feet

Available Colors

(colors are approximations)



*Exact representation of colors in printing is difficult. Please refer to actual color samples for accurate matching. **Samples available upon request.***