



**The LiteLink® Slat is one of the most economical chain-link enhancement products available in the market today.**

Manufactured using the same durable outdoor plastic as our standard tubular fence slats, this single wall “M” shaped slat will give you the visual screening and color enhancement you desire at a very affordable price. LiteLink also uses our innovative Bottom Locking system for fast and easy installation.

**Design**

Compact and lightweight, LiteLink’s unique shape enables the slat to self stack. It comes in a box (2" x 5" x slat length) making it easy to ship and efficient to store.

**Standard Heights**

4, 5, 6, 7, 8, 10 and 12 feet. Special heights available upon request.

**Slat Length**

3½” shorter than the overall height of fence.

**Bottom Locking Channel**

10 feet provided in each bag.

**Wind Load & Privacy Factor**

Approximately 75%.



**Colors\***



\* Exact representation of slat colors in printing is difficult. Please refer to actual color samples for final matching. Covered by one or more of the following patents: US Patent 6,068,243 / 5,165,664 / 5,234,199



*PDS® is a registered trademark of Pexco.*

**Made in the USA**





# PRODUCT SPECIFICATIONS

Slat Type	Slat Width	Mesh Size	Wire Gauge	Slats Per Bag	Approx. Coverage Per Box
LiteLink®	1¼"	2", 2¼" or 2¾"	9, 11 or 11½	82	10 linear feet

## Materials

The LiteLink product is extruded from High Density Polyethylene (HDPE), color pigments and ultra violet (UV) inhibitors, specifically designed to retard the harmful effects of the sun and lengthen the life of the product.

## Durability

Pexco PDS® HDPE Fence Products are resistant to: severe weather conditions, salt water, sand, road dirt, most acids, alcohol, alkaline, ammonia, petroleum distillates, and common environmental pollutants.

## Maintenance

Pressure cleaning of surface contaminants is quickly accomplished with plain water.

## Wind Load Disclaimer

Pexco will not be responsible for damage due to wind load conditions resulting from insufficient structural support.


## Limited Warranty

LiteLink carries a 7-year, pro-rata warranty against breakage under normal conditions. Write Pexco for full warranty information.

## Installation Instructions


### Step 1

Insert rail horizontally in first full diamond at bottom of fence with open side facing up.



### Step 2

Insert vertical slats with interlocking tab downward. Slat engages and interlocks with bottom rail.



### Step 3

Push the vertical slat into the horizontal channel to lock-in place.



## HDPE Technical Properties

Property	Value
Melt Index	(.35) Optimum extrusion processing conditions for Fence Slats
Density	(.945) Polyethylene ranges anywhere from .914 to .960 in density
Minimum Temp.	(-70°) Under no stress, HDPE remains flexible at this temperature
Maximum Temp.	(180°) Under no stress, HDPE will not distort at this temperature
Tensile Strength	(3,700 psi) HDPE will not distort at lesser loads or impacts

www.PrivacySlatKing.com  
 (800) 878-7829  
 Sales@PrivacySlatKing.com

Feel free to contact us for more information about our complete line of slats and other chain link fence enhancement products.

