

INDUSTRIAL PRE-WOVEN FENCE SLATS



Specifications

Design: Industrial Pre-Woven Slats are flat and tubular in shape, with three "legs" inside the hollow body of the slat, for extra durability.

Standard Heights: 4, 5, 6, 8, 10 & 12 feet. Special heights available upon request.

Wind Load & Privacy Factor: Approximately 75%

Upon Special Request: Available in bags that cover 25 linear feet for smaller jobs.



SLAT PROFILE:



COLORS:*

The Industrial Pre-Woven Slat is a standard style economical slat, for commercial or industrial applications.



This slat is mechanically inserted into the chain link wire during the weaving process. Once inserted, the wire is finished above and below the slat (either bow-knuckle or knuckle-over).

Black

White

Gray

Beige

Brown

Redwood

Green

Royal Blue

Light Blue

INDUSTRIAL PRE-WOVEN SLAT FENCE SLATS

SLAT TYPE	SLAT WIDTH	MESH SIZE	WIRE GAUGE	SLATS PER BAG	APPROX. COVERAGE PER BOX
Industrial Pre-Woven	2 ³ / ₈ "	3 ¹ / ₂ " x 5"	9 or 10	2,014 (106 pieces/bag)	475 linear feet (25 linear feet/bag)

QUALITY MATERIALS

The Industrial Pre-Woven product is extruded from High Density Polyethylene (HDPE), color pigments, and ultra violet (UV) inhibitors, specifically designed to retard the harmful effects of the sun and lengthen the life of the product.

HIGH DURABILITY

Pexco PDS® HDPE Fence Products are resistant to severe weather conditions, salt water, sand, road dirt, most acids, alcohol, alkaline, ammonia, petroleum distillates, and common environmental pollutants.

EASY MAINTENANCE

Pressure cleaning of surface contaminants is quickly accomplished with plain water.



HDPE TECHNICAL PROPERTIES

Melt Index

(.35) Optimum extrusion processing conditions for Fence Slats

Density

(.945) Polyethylene ranges anywhere from .914 to .960 in density

Minimum Temp.

(-70°) Under no stress, HDPE remains flexible at this temperature


Maximum Temp.

(180°) Under no stress, HDPE will not distort at this temperature

Tensile Strength

(4,000 psi) HDPE will not distort at lesser loads or impacts

INSTALLATION INSTRUCTIONS



STEP 1: Because this slat comes pre-inserted in the chain link fabric, just stretch the wire and tie it up. The result is a fully slatted fence with 75% privacy.

NOTE: Pexco is the manufacturer of the plastic slats only; we do not weave the wire. For pre-woven products, please contact your fence supplier or contact us for a supplier near you.

* Exact representation of slat colors in printing is difficult. Please refer to actual color samples for final matching.
Covered by one or more of the following patents: US Patent **6,068,243 / 5,165,664 / 5,234,199**

** Industrial Pre-Woven carries a 25-year, pro-rata warranty against breakage under normal conditions. Write Pexco for full warranty information.
Wind Load Disclaimer: Pexco will not be responsible for damage due to wind load conditions resulting from insufficient structural support.