

FINLINK® (Extra-Privacy)



The FinLink® Slat offers extra screening and security with a unique configuration of (3) three privacy fins.

FinLink provides a quality looking installation and is used together with our proprietary bottom channel. This process ensures that all slats are even in the wire and will not slip to the ground.

Design

Our unique innovative design includes a rigid, flat tubular body, with “legs” inside for extra support. Three flexible fins (two on one side and one on the other) are positioned on the side of the slat body. The FinLink fins are not serrated, thus providing a smooth finished look.

Standard Heights

4, 5, 6, 7 and 8 feet.

Slat Length

3½” shorter than the overall height of fence.

Bottom Locking Channel

10 feet provided in each bag.

Wind Load & Privacy Factor

Approximately 90%.

SLAT
PROFILE:



Colors*



* Exact representation of slat colors in printing is difficult. Please refer to actual color samples for final matching.
Covered by one or more of the following patents: US Patent 6,068,243 / 5,165,664 / 5,234,199

Made in the USA



PRODUCT SPECIFICATIONS

Slat Type	Slat Width	Mesh Size	Wire Gauge	Slats Per Bag	Approx. Coverage Per Box
FinLink®	1 3/8"	2"	11, 11 1/2 or 12	82	10 linear feet

Materials

The FinLink product is extruded from High Density Polyethylene (HDPE), color pigments and ultra violet (UV) inhibitors, specifically designed to retard the harmful effects of the sun and lengthen the life of the product.

Durability

Pexco PDS® HDPE Fence Products are resistant to: severe weather conditions, salt water, sand, road dirt, most acids, alcohol, alkaline, ammonia, petroleum distillates, and common environmental pollutants.

Maintenance

Pressure cleaning of surface contaminants is quickly accomplished with plain water.

Wind Load Disclaimer

We will not be responsible for damage due to wind load conditions resulting from insufficient structural support.

Limited Warranty

FinLink carries a 25-year, pro-rata warranty against breakage under normal conditions. Write Pexco for full warranty information.


Note

These are friction-fitting Fence Slats. Additional time should be allowed for installation.

Installation Instructions


Step 1

Insert rail horizontally in first full diamond at bottom of fence with open side facing up.



Step 2

Insert vertical slats with bevel end downward.



Step 3

Push the vertical slat into the horizontal channel.



HDPE Technical Properties

Property	Value
Melt Index	(.35) Optimum extrusion processing conditions for Fence Slats
Density	(.945) Polyethylene ranges anywhere from .914 to .960 in density
Minimum Temp.	(-70°) Under no stress, HDPE remains flexible at this temperature
Maximum Temp.	(180°) Under no stress, HDPE will not distort at this temperature
Tensile Strength	(3,700 psi) HDPE will not distort at lesser loads or impacts