

TOP LOCK



The Top Lock Slat provides an economical and attractive way to enhance any chain link fence.

With over 40 years of experience extruding these innovative, proprietary products, you are assured of the highest standards in quality—from the raw materials used in manufacturing to the finished product in your fence. This design utilizes a top locking mechanism located near the top of the slats to ensure a clean, straight edge, further enhancing its appearance.

Design

Top Lock Slats are flat and tubular in shape, with circular, notched-out holes located near the top of the slat.

Standard Heights

4, 5, 6, 7, 8, 10 & 12 feet. Special heights available upon request.

Slat Length

2" shorter than the overall height of fence.

Flexible Top Locking Channel

10 feet provided in each bag.

Wind Load & Privacy Factor

Approximately 75%.



Colors*



* Exact representation of slat colors in printing is difficult. Please refer to actual color samples for final matching. Covered by one or more of the following patents: US Patent 6,068,243 / 5,165,664 / 5,234,199

Made in the USA



PRODUCT SPECIFICATIONS

Slat Type	Slat Width	Mesh Size	Wire Gauge	Slats Per Bag	Approx. Coverage Per Box
Top Lock 2"	1 ³ / ₃₂ "	2"	8, 9 or 11	82	10 linear feet
Top Lock 2 ¹ / ₄ "	1 ¹ / ₄ "	2 ¹ / ₄ " or 2 ³ / ₈ "	11 ¹ / ₂ or 12 ¹ / ₂	78	10 linear feet
Top Lock 1 ³ / ₄ "	7/8"	1 ³ / ₄ "	8, 9 or 11	100	10 linear feet
	7/8"	2"	6	100	10 linear feet

Materials

The Top Lock product is extruded from High Density Polyethylene (HDPE), color pigments and ultra violet (UV) inhibitors, specifically designed to retard the harmful effects of the sun and lengthen the life of the product.

Durability

Pexco PDS® HDPE Fence Products are resistant to: severe weather conditions, salt water, sand, road dirt, most acids, alcohol, alkaline, ammonia, petroleum distillates, and common environmental pollutants.

Maintenance

Pressure cleaning of surface contaminants is quickly accomplished with plain water.

Wind Load Disclaimer

Pexco will not be responsible for damage due to wind load conditions resulting from insufficient structural support.


Limited Warranty

Top Lock carries a 25-year, pro-rata warranty against breakage under normal conditions. Write Pexco for full warranty information.

Installation Instructions


Step 1

There is no need to kneel down! Simply insert the slats vertically from top to bottom, keeping the locking holes on top.



Step 2

Thread the flexible locking channel horizontally through the notched holes in the slats.



These holes are elliptical to ensure they always stay open for fast and easy threading.

HDPE Technical Properties

Property	Value
Melt Index	(.35) Optimum extrusion processing conditions for Fence Slats
Density	(.945) Polyethylene ranges anywhere from .914 to .960 in density
Minimum Temp.	(-70°) Under no stress, HDPE remains flexible at this temperature
Maximum Temp.	(180°) Under no stress, HDPE will not distort at this temperature
Tensile Strength	(3,700 psi) HDPE will not distort at lesser loads or impacts