

WINGED SLAT®

(Extra-Privacy)



When you need increased privacy, our Winged Slat® is the answer.

With the proven quality and durability of our standard slats plus unique “wings” for extra screening and security, these slats are self-locking – no channels are needed!

Design

Our innovative Winged Slat has a rigid, flat tubular body, with “legs” inside for extra support and durability. Flexible and resilient wing portions are positioned on each side of the slat body. Serrations are added to the wings for easier installation and locking power.

Standard Heights

4, 5, 6, 7 and 8 feet.

Slat Length

2” shorter than the overall height of fence.

Wind Load & Privacy Factor

Approximately 90%. (Based on wire/mesh used – stretch tension).



Colors*



* Exact representation of slat colors in printing is difficult. Please refer to actual color samples for final matching. Covered by one or more of the following patents: US Patent 6,068,243 / 5,165,664 / 5,234,199

Made in the USA



PRODUCT SPECIFICATIONS

Slat Type	Slat Width	Mesh Size	Wire Gauge	Slats Per Bag	Approx. Coverage Per Box
Winged Slat®	1 3/8"	2"	9 only	82	10 linear feet

Materials

The Winged Slat product is extruded from High Density Polyethylene (HDPE), color pigments and ultra violet (UV) inhibitors, specifically designed to retard the harmful effects of the sun and lengthen the life of the product.

- Winged Slats include Ethyl Vinyl Acetate (EVA), a softer plastic to keep the wings flexible and resilient.

Durability

Pexco PDS® HDPE Fence Products are resistant to: severe weather conditions, salt water, sand, road dirt, most acids, alcohol, alkaline, ammonia, petroleum distillates, and common environmental pollutants.

Maintenance

Pressure cleaning of surface contaminants is quickly accomplished with plain water.

Wind Load Disclaimer

Pexco will not be responsible for damage due to wind load conditions resulting from insufficient structural support.

Limited Warranty


Winged Slat carries a 25-year, pro-rata warranty against breakage under normal conditions. Write Pexco for full warranty information.

Note

These are friction-fitting Fence Slats. Additional time should be allowed for installation.

Installation Instructions

Insert vertical slats with angle cut end downward. Winged portion interlocks with chain link knuckles.



Important: For Fence heights higher than 8 feet, we strongly advise **NOT** to double-stack Winged Slats®. If you double-stack, you will be at risk of the Winged Slats® not all giving the same visual appearance or giving the same privacy effect on the top and bottom portions of the Fence.

HDPE Technical Properties

Property	Value
Melt Index	(.35) Optimum extrusion processing conditions for Fence Slats
Density	(.945) Polyethylene ranges anywhere from .914 to .960 in density
Minimum Temp.	(-70°) Under no stress, HDPE remains flexible at this temperature
Maximum Temp.	(180°) Under no stress, HDPE will not distort at this temperature
Tensile Strength	(3,700 psi) HDPE will not distort at lesser loads or impacts